

HTT/E AL

Aluminium » otwarte » kołnierz płaski » gładkie

Aluminium » open end » flat head » smooth



Gwint Thread									kod		€ / 100szt.
M3	4,9	8,3	0,3-1,8	5,0	8,0	0,75			HTT/E-1,8 M3 AL	250	4,2
		9,7	1,8-3,0		7,0	0,80			HTT/E-3,0 M3 AL		4,4
M4	5,9	9,7	0,5-2,0	6,0	8,5	0,80			HTT/E-2,0 M4 AL	250	4,6
		12,0	2,5-4,0		9,0	1,00			HTT/E-4,0 M4 AL		4,8
M5	6,9	12,0	0,5-2,5	7,0	10,0	1,00			HTT/E-2,5 M5 AL	250	5,2
		14,3	3,0-5,0			1,20			HTT/E-5,0 M5 AL		5,8
M6	8,9	13,6	0,5-2,5	9,0	12,3	1,40			HTT/E-2,5 M6 AL	250	6,8
		14,5	2,5-4,0		12,0	1,50			HTT/E-4,0 M6 AL		7,1
M8	10,9	15,0	1,0-2,5	11,0	14,3	1,50			HTT/E-2,5 M8 AL	250	8,8
		18,5	3,5-6,0		15,0				HTT/E-6,0 M8 AL		9,5
M10	11,9	17,3	0,8-3,5	12,0	16,0	1,70			HTT/E-3,5 M10 AL	100	10,0
		20,3	3,5-6,0						HTT/E-6,0 M10 AL		11,2
M10	12,9	17,9	1,0-4,0	13,0	17,0	1,60			HTT/E-4,0 M10 AL	100	10,9
		25,5	4,5-7,5		19,0	2,00			HTT/E-7,5 M10 AL		11,6
M12	15,9	24,0	1,0-4,0	16,0	23,0	2,00			HTT/E-4,0 M12 AL	100	18,0
		27,0	3,5-7,0						HTT/E-7,0 M12 AL		19,6