

HTT-Z/E AL

Aluminium » otwarte » kołnierz płaski » radełkowane

Aluminium » open end » flat head » knurled



Gwint Thread									kod		€ / 100szt.
M3	4,9	10,00	0,5-3,0	5,0	7,0	0,90			HTT-Z/E-3,0 M3 AL	250	9,8
M4	5,9	10,0	0,3-3,0	6,0	9,0	1,00			HTT-Z/E-3,0 M4 AL	250	11,2
		11,5	3,1-4,0						HTT-Z/E-4,0 M4 AL	250	12,2
M5	6,9	12,0	0,3-3,0	7,0	10,0	1,00			HTT-Z/E-3,0 M5 AL	250	12,2
		15,0	3,1-4,0						HTT-Z/E-4,0 M5 AL	250	12,6
M6	8,9	14,5	0,5-3,0	9,0	13,0	1,50			HTT-Z/E-3,0 M6 AL	250	16,0
		16,0	3,1-4,5						HTT-Z/E-4,5 M6 AL	250	16,3
		19,5	5,0-8,0						HTT-Z/E-8,0 M6 AL	250	23,5
M8	10,9	16,0	0,5-3,0	11,0	16,0	1,50			HTT-Z/E-3,0 M8 AL	250	18,2
		18,5	3,1-5,5						HTT-Z/E-5,5 M8 AL	250	21,4
		21,0	5,0-8,0						HTT-Z/E-8,0 M8 AL	250	27,2
M10	12,9	17,0	0,5-3,0	13,0	19,0	2,00			HTT-Z/E-3,0 M10 AL	100	26,8
		22,0	3,1-6,0						HTT-Z/E-6,0 M10 AL	100	27,4
M12	15,9	23,0	1,0-4,0	16,0	23,0	2,00			HTT-Z/E-4,0 M12 AL	100	43,2