










HTT-Z/E ZI

Stal ocynkowana » otwarte » kołnierz płaski » radełkowane

Steel zinc plated » open end » flat head » knurled



Gwint Thread									kod		€ / 100szt.			
M3	4,9	9,2	0,5-1,5	5,0	8,0	0,8			HTT-Z/E-1,5 M3 ZI	250	3,6			
		11,2	2,0-4,5		7,0				HTT-Z/E-4,5 M3 ZI	250	3,9			
M4	5,9	9,7	0,5-2,0	6,0	9,0	0,8			HTT-Z/E-2,0 M4 ZI	250	3,9			
		11,2	2,5-3,5						HTT-Z/E-3,5 M4 ZI	250	4,4			
M5	6,9	12,0	0,5-2,5	7,0	10,0	1,0			HTT-Z/E-2,5 M5 ZI	250	4,4			
		15,5	2,5-5,0						HTT-Z/E-5,0 M5 ZI	250	5,2			
M6	8,9	14,2	0,5-3,0	9,0	12,3	1,3			HTT-Z/E-3,0 M6 ZI	250	5,2			
		18,2	3,0-5,5						HTT-Z/E-5,5 M6 ZI	250	5,8			
M8	10,9	17,0	1,0-3,5	11,0	14,5	1,5			HTT-Z/E-3,5 M8 ZI	250	5,8			
		19,5	3,5-6,0						HTT-Z/E-6,0 M8 ZI	250	6,8			
M10	11,9	16,6	0,5-3,5	12,0	16,0	1,7			HTT-Z/E12-3,5 M10 ZI	100	7,6			
		23,2	4,0-6,5						HTT-Z/E12-6,5 M10 ZI	100	8,2			
		12,9	19,8		1,0-4,0				13,0	17,0	1,7	HTT-Z/E13-4,0 M10 ZI	100	7,9
		22,3	4,0-6,5						HTT-Z/E13-6,5 M10 ZI	100	8,6			
M12	14,9	20,3	1,0-4,0	15,0	18,0	1,7			HTT-Z/E-4,0 M12 ZI	100	11,2			
		15,9	23,0		1,0-3,5				16,0	22,0	2,0	HTT-Z/E-3,5 M12 ZI	100	12,6
		26,0	3,5-6,0									HTT-Z/E-6,0 M12 ZI	100	14,6