

HTTEC/E ZI

Stal ocynkowana » zamknięte » kołnierz płaski » sześciokąt

Steel zinc plated » closed end » flat head » hexagon



Gwint Thread									kod		€ / 100szt.
M3	4,9	12,0	0,5-2,0	5,0	8,0	0,8			HTTEC/ES-2,0 M3 ZI	250	spec.
M3	4,9	13,7	2,0-3,5	5,0	8,0	0,8			HTTEC/ES-3,5 M3 ZI	250	spec.
M4	5,9	14,0	0,5-2,0	6,0	9,0	1,0			HTTEC/E-2,0 M4 ZI	250	34,0
M4	5,9	16,0	2,0-4,0	6,0	9,0	1,0			HTTEC/ES-4,0 M4 ZI	250	spec.
M5	6,9	17,0	0,5-2,5	7,0	10,0	1,0			HTTEC/E-2,5 M5 ZI	250	42,0
M5	6,9	19,0	2,5-4,5	7,0	10,0	1,0			HTTEC/ES-4,5 M5 ZI	250	spec.
M6	8,9	21,5	0,5-3,0	9,0	12,7	1,5			HTTEC/E-3,0 M6 ZI	250	55,0
M6	8,9	24,0	3,0-5,5	9,0	12,7	1,5			HTTEC/ES-5,5 M6 ZI	250	spec.
M8	10,9	24,5	1,0-3,5	11,0	16,0	1,5			HTTEC/E-3,5 M8 ZI	250	63,0
M8	10,9	26,0	3,5-6,0	11,0	16,0	1,5			HTTEC/ES-6,0 M8 ZI	250	spec.
M10	12,9	31,0	1,0-4,0	13,0	19,0	2,0			HTTEC/E-4,0 M10 ZI	100	69,0
M10	12,9	31,0	3,5-6,0	13,0	19,0	2,0			HTTEC/ES-6,0 M10 ZI	100	spec.
M12	15,9	36,5	0,5-3,5	16,0	23,0	2,0			HTTEC/ES-3,5 M12 ZI	100	spec.
M12	15,9	39,5	3,5-6,5	16,0	23,0	2,0			HTTEC/ES-6,5 M12 ZI	100	spec.