

## HTTSE/E A2

Stal nierdzewna » otwarte » kolnierz płaski » częściowy sześciokąt

Stainless Steel » open end » flat head » partial hexagon



Gwint Thread									kod		€ / 100szt.
M3	4,9	8,3	0,3-1,8	5,0	8,0	0,75			HTTSE/E-1,8 M3 A2	250	14,2
		9,3	1,8-3,0						HTTSE/E-3,0 M3 A2	250	15,6
M4	5,9	10,2	0,5-2,0	6,0	8,7	0,80			HTTSE/E-2,0 M4 A2	250	16,6
		11,8	2,5-4,0						HTTSE/E-4,0 M4 A2	250	17,5
M5	6,9	11,0	0,5-2,5	7,0	10,0	1,00			HTTSE/E-2,5 M5 A2	250	18,2
		14,0	2,0-4,0						HTTSE/E-4,0 M5 A2	250	19,1
M6	8,9	14,2	0,5-3,0	9,0	12,7	1,30			HTTSE/E-3,0 M6 A2	250	22,6
		17,5	3,5-6,0						HTTSE/E-6,0 M6 A2	250	26,2
M8	10,9	16,5	1,0-3,5	11,0	16,0	1,50			HTTSE/E-3,5 M8 A2	250	29,2
		18,5	3,0-6,0						HTTSE/E-6,0 M8 A2	250	34,2
M10	11,9	17,3	0,8-3,5	12,0	16,0	1,70			HTTSE/E12-3,5 M10 A2	100	48,2
		20,3	3,5-6,0						HTTSE/E12-6,0 M10 A2	100	49,6
M10	12,9	19,3	1,0-3,5	13,0	18,0	1,70			HTTSE/E13-3,5 M10 A2	100	49,2
		24,0	3,0-6,0						HTTSE/E13-6,0 M10 A2	100	52,3
M12	15,9	24,0	1,0-4,0	16,0	23,0	2,00			HTTSE/E-4,0 M10 A2	100	64,2
		27,0	3,5-7,0						HTTSE/E-7,0 M10 A2	100	68,9