

HTTSE/E ZI

Stal ocynkowana » otwarte » kołnierz płaski » częściowy sześciokąt

Steel zinc plated » open end » flat head » partial hexagon



Gwint Thread										kod		€ / 100szt.
M3	4,9	8,2	0,3-1,8	5,0	8,0	0,75				HTTSE/E-1,8 M3 ZI	250	4,6
M4	5,9	10,2	0,5-2,0	6,0	9,0	0,80				HTTSE/E-2,0 M4 ZI	250	5,0
M5	6,9	12,0	0,5-2,5	7,0	10,0	1,00				HTTSE/E-2,5 M5 ZI	250	6,2
M6	8,9	13,7	0,5-3,0	9,0	12,7	1,30				HTTSE/E-3,0 M6 ZI	250	6,9
M8	10,9	16,5	1,0-3,5	11,0	16,0	1,50				HTTSE/E-3,5 M8 ZI	250	8,9
M10	11,9	18,5	0,5-3,5	12,0	16,5	1,80				HTTSE/E12-3,5 M10 ZI	100	9,4
	12,9	18,5	0,5-3,5	13,0	17,0	1,80				HTTSE/E13-3,5 M10 ZI	100	9,8
M12	14,9	25,3	2,0-5,0	16,0	23,0	2,20				HTTSE/E-5,0 M12 ZI	100	18,6