

HTTC-Z/E ZI

Stal ocynkowana » zamknięte » kołnierz płaski » radełkowane

Steel zinc plated » closed end » flat head » knurled



Gwint Thread									kod		€ / 100szt.
M3	4,9	12,2	0,5-2,0	5,0	8,0	0,8			HTTC-Z/ES-2,0 M3 ZI	250	spec.
M3	4,9	13,7	2,0-3,5	5,0	8,0	0,8			HTTC-Z/ES-3,5 M3 ZI	250	spec.
M4	5,9	15,2	0,5-2,0	6,0	9,0	0,8			HTTC-Z/E-2,0 M4 ZI	250	31,0
M4	5,9	16,2	2,0-4,0	6,0	9,0	0,8			HTTC-Z/ES-4,0 M4 ZI	250	spec.
M5	6,9	16,0	0,5-3,0	7,0	10,0	1,0			HTTC-Z/E-3,0 M5 ZI	250	38,0
M5	6,9	19,0	2,5-4,5	7,0	10,0	1,0			HTTC-Z/ES-4,5 M5 ZI	250	38,0
M6	8,9	17,7	0,5-3,0	9,0	12,3	1,3			HTTC-Z/E-3,0 M6 ZI	250	49,0
M6	8,9	23,8	3,0-5,5	9,0	12,0	1,2			HTTC-Z/ES-5,5 M6 ZI	250	spec.
M8	10,9	20,0	0,5-3,0	11,0	15,0	1,5			HTTC-Z/E-3,0 M8 ZI	250	57,0
M8	10,9	26,2	3,5-6,0	11,0	14,0	1,3			HTTC-Z/ES-6,0 M8 ZI	250	spec.
M10	12,9	25,4	1,0-4,0	13,0	17,0	1,6			HTTC-Z/E-4,0 M10 ZI	100	63,0
M10	12,9	31,0	3,5-6,0	13,0	16,0	1,5			HTTC-Z/ES-6,0 M10 ZI	100	spec.