










# NITY STANDARDOWE – KOŁNIERZ STOŻKOWY 120°

Aluminium (AlMg 5,0) / Stal nierdzewna A2 (1.4301) - EN ISO 15984

# STANDARD BLIND RIVETS – COUNTERSUNK HEAD 120°

Aluminium (AlMg 5,0) / Stainless steel A2 (1.4301) - EN ISO 15984



								kod	
3,2 (+0,08/-0,10)	6,0	0,0-3,0	6,0 (+0/-0,4)	1,0	3,3	980	760	AN-WP032006	1000
	8,0	3,0-5,0						AN-WP032008	1000
	10,0	5,0-7,0						AN-WP032010	1000
	12,0	7,0-9,0						AN-WP032012	1000
4,0 (+0,08/-0,15)	6,0	0,0-2,0	7,5 (+0/-0,5)	1,2	4,1	1600	1200	AN-WP040006	1000
	8,0	2,0-4,0						AN-WP040008	1000
	10,0	4,0-6,0						AN-WP040010	1000
	12,0	6,0-8,0						AN-WP040012	1000
4,8 (+0,08/-0,15)	8,0	0,0-3,5	9,0 (+0/-0,5)	1,2	4,9	2230	1690	AN-WP048008	500
	10,0	3,5-5,5						AN-WP048010	500
	12,0	5,5-7,5						AN-WP048012	500
	14,0	7,5-9,5						AN-WP048014	500
	16,0	9,0-11,0						AN-WP048016	500
	18,0	11,0-13,0						AN-WP048018	500
	20,0	13,0-15,0						AN-WP048020	500