










NITY STANDARDOWE – KOŁNIERZ STOŻKOWY 120°

Aluminium (AlMg 3,5) / Stal ocynkowana - EN ISO 15978

STANDARD BLIND RIVETS – COUNTERSUNK HEAD 120°

Aluminium (AlMg 3,5) / Steel zinc plated – EN ISO 15978



								kod	
2,4 (+0,08/-0,10)	6,0	0,0-3,5	5,0 (+0/-0,4)	1,0	2,5	353,0	315,0	AS-WP024006	1000
	8,0	3,5-5,5						AS-WP024008	1000
	10,0	5,5-7,5						AS-WP024010	1000
3,0 (+0,08/-0,10)	6,0	0,0-3,5	6,0 (+0/-0,4)	1,0	3,1	810	620	AS-WP030006	1000
	8,0	3,5-5,5						AS-WP030008	1000
	10,0	5,5-7,5						AS-WP030010	1000
	12,0	7,5-9,5						AS-WP030012	1000
	14,0	9,0-12,0						AS-WP030014	1000
3,2 (+0,08/-0,10)	6,0	0,0-3,0	6,0 (+0/-0,4)	1,0	3,3	980	760	AS-WP032006	1000
	8,0	3,0-5,0						AS-WP032008	1000
	10,0	5,0-7,0						AS-WP032010	1000
	12,0	7,0-9,0						AS-WP032012	1000
	14,0	9,0-11,0						AS-WP032014	1000
	16,0	11,0-13,0						AS-WP032016	1000
4,0 (+0,08/-0,15)	6,0	0,0-2,0	7,5 (+0/-0,5)	1,2	4,1	1600	1200	AS-WP040006	1000
	8,0	2,0-4,0						AS-WP040008	1000
	10,0	4,0-6,0						AS-WP040010	1000
	12,0	6,0-8,0						AS-WP040012	1000
	14,0	8,0-10,0						AS-WP040014	500
	16,0	10,0-12,0						AS-WP040016	500
	18,0	12,0-14,0						AS-WP040018	500
	20,0	14,0-16,5						AS-WP040020	500
4,8 (+0,08/-0,15)	8,0	0,0-3,5	9,0 (+0/-0,5)	1,5	4,9	2230	1690	AS-WP048008	500
	10,0	3,5-5,5						AS-WP048010	500
	12,0	5,5-7,5						AS-WP048012	500
	14,0	7,5-9,5						AS-WP048014	500
	16,0	9,0-11,0						AS-WP048016	500
	18,0	11,0-13,0						AS-WP048018	500
	20,0	13,0-15,0						AS-WP048020	500
	22,0	15,0-17,0						AS-WP048022	500
	25,0	17,0-20,0						AS-WP048025	500
	30,0	20,0-25,0						AS-WP048030	250
	35,0	25,0-30,0						AS-WP048035	250










NITY STANDARDOWE – KOŁNIERZ STOŻKOWY 120°

Aluminium (AlMg 3,5) / Stal ocynkowana - EN ISO 15978

STANDARD BLIND RIVETS – COUNTERSUNK HEAD 120°

Aluminium (AlMg 3,5) / Steel zinc plated – EN ISO 15978



								kod	
5,0 (+0,08/-0,15)	8,0	0,0-3,5	9,0 (+0/-0,5)	1,5	5,1	2500	2000	AS-WP050008	500
	10,0	3,5-5,5						AS-WP050010	500
	12,0	5,5-7,5						AS-WP050012	500
	14,0	7,5-9,5						AS-WP050014	500
	16,0	9,0-11,0						AS-WP050016	500
	18,0	11,0-13,0						AS-WP050018	500
	20,0	13,0-15,0						AS-WP050020	250
	25,0	15,0-20,0						AS-WP050025	250
	30,0	20,0-25,0						AS-WP050030	250