










NITY STANDARDOWE – KOŁNIERZ PŁASKI

Miedź / Stal ocynkowana - EN ISO 16582

STANDARD BLIND RIVETS – DOME HEAD

Copper / Steel zinc plated – EN ISO 16582



								kod	
3,0 (+0,08/-0,10)	4,0	0,5-1,5	6,5 (+0/-0,7)	0,8 (+/-0,20)	3,1	700	600	CUS030004	1000
	5,0	0,5-2,0						CUS030005	1000
	6,0	1,5-3,5						CUS030006	1000
	8,0	3,5-5,5						CUS030008	1000
	10,0	5,5-7,5						CUS030010	1000
	12,0	7,5-9,5						CUS030012	1000
3,2 (+0,08/-0,10)	6,0	1,5-3,0	6,5 (+0/-0,7)	0,8 (+/-0,20)	3,3	800	700	CUS032006	1000
	8,0	3,0-5,0						CUS032008	1000
	10,0	5,0-7,0						CUS032010	1000
	12,0	7,0-9,0						CUS032012	1000
4,0 (+0,08/-0,15)	6,0	1,0-2,0	8,0 (+0/-1,0)	1,0 (+/-0,30)	4,1	1500	1000	CUS040006	1000
	8,0	2,0-4,0						CUS040008	1000
	10,0	4,0-6,0						CUS040010	1000
	12,0	6,0-8,0						CUS040012	1000
	14,0	8,0-10,0						CUS040014	500
	16,0	10,0-12,0						CUS040016	500
4,8 (+0,08/-0,15)	8,0	2,0-3,5	9,5 (+0/-1,0)	1,1 (+/-0,30)	4,9	2000	1500	CUS048008	500
	10,0	3,5-5,5						CUS048010	500
	12,0	5,5-7,5						CUS048012	500
	14,0	7,5-9,5						CUS048014	500
	16,0	9,0-11,0						CUS048016	500
	18,0	11,0-13,5						CUS048018	500
	20,0	13,5-15,5						CUS048020	500