


NITY ROWKOWANE – KOŁNIERZ PŁASKKI

Aluminium (AlMg 2,5) / Stal ocynkowana

GROOVED BLIND RIVETS – DOMED HEAD

Aluminium (AlMg 2,5) / Steel zinc plated



								kod	
3,2 (+0,35/-0,0)	10,0	max. 6,0	6,0 (+/-0,24)	1,4	3,4	930	670	AS-R032010	1000
	14,0	max. 10,0						AS-R032012	1000
4,0 (+0,35/-0,0)	8,0	max. 4,0	8,0 (+/-0,29)	1,7	4,3	1400	1200	AS-R040010	1000
	10,0	max. 6,0						AS-R040012	1000
	12,0	max. 8,0						AS-R040014	500
	16,0	max. 12,0						AS-R040016	500
4,8 (+0,35/-0,0)	8,0	max. 4,0	9,5 (+/-0,29)	2,0	5,1	2300	1600	AS-R048010	500
	10,0	max. 6,0						AS-R048012	500
	12,0	max. 8,0						AS-R048014	500
	14,0	max. 10,0						AS-R048016	500
	16,0	max. 12,0						AS-R048018	500
	18,0	max. 14,0						AS-R048020	500
	20,0	max. 16,0						AS-R048022	500
	25,0	max. 21,0						AS-R048025	500
	30,0	max. 26,0						AS-R048030	250