

# WSUWKI - SPRINGS

## KRAŻEK ZABEZPIEZAJĄCY Z KAPTURKIEM



**Material:** stal sprężynowa  
**Powłoka:** stal niklowana

**Material:** spring steel  
**Surface:** steel nickel

Ø	Kod produktu Reference	Wymiary - Dimensions		
		A	B	C
2,0	HS - CP - 210	12,0	5,0	3,0
2,5	HS - CP - 251	12,0	5,0	3,0
3,0	HS - CP - 309	12,0	5,0	3,0
4,0	HS - CP - 410	12,0	5,0	3,0
5,0	HS - CP - 510	12,0	5,0	3,0
	HS - CP - 515	16,0	6,0	4,0
6,0	HS - CP - 615	16,0	6,0	4,0
6,5	HS - CP - 651	16,0	6,0	4,0
7,0	HS - CP - 715	16,0	6,0	4,0
8,0	HS - CP - 815	16,0	6,0	4,0
9,0	HS - CP - 918	19,0	7,0	4,5
9,5	HS - CP - 951	19,0	7,0	4,5
10,0	HS - CP - 1018	19,0	7,0	4,5
11,0	HS - CP - 1118	19,0	7,0	4,5
12,0	HS - CP - 1220	22,0	8,0	4,5
	HS - CP - 1225	27,0	9,5	6,0
13,0	HS - CP - 1325	27,0	9,5	6,0
14,0	HS - CP - 1425	27,0	9,5	6,0
15,0	HS - CP - 1525	27,0	9,5	5,0
	HS - CP - 1528	30,0	10,0	6,0
16,0	HS - CP - 1625	27,0	9,5	5,0
	HS - CP - 1628	30,0	10,0	6,0

Ø	Kod produktu Reference	Wymiary - Dimensions		
		A	B	C
17,0	HS - CP - 1728	30,0	10,0	6,0
18,0	HS - CP - 1825	27,0	9,5	5,0
	HS - CP - 1828	30,0	10,0	6,0
20,0	HS - CP - 2036	38,0	10,0	6,0
22,0	HS - CP - 2236	38,0	10,0	6,0
25,0	HS - CP - 2541	43,0	12,0	7,0

