

WSUWKI - SPRINGS DO KOŁKÓW



Material: stal sprężynowa
Powłoka: fosforatowana, ocynk biały

Material: spring steel
Surface: phosphated, zinc plated

Ø	Kod produktu Reference	Wymiary - Dimensions		
		A	B	S
2,0	HS - PL - 2128	12,5	8,0	0,5
	HS - PL - 2128	15,0	8,0	0,4
2,3	HS - PL - 2315	15,0	8,0	0,4
2,5	HS - PL - 2512	12,5	8,0	0,4
3,0	HS - PL - 3138	13,0	8,0	0,4
	HS - PL - 3158	15,0	8,0	0,4
3,5	HS - PL - 3515	15,0	8,0	0,4
	HS - PL - 3520	20,0	13,0	0,4
3,8	HS - PL - 3817	17,5	10,0	0,5
4,0	HS - PL - 4120	20,0	10,0	0,4
	HS - PL - 4159	15,0	9,5	0,4
	HS - PL - 4181	18,0	10,0	0,4
4,5	HS - PL - 4518	18,0	10,0	0,4
4,75	HS - PL - 4571	18,0	10,0	0,4
5,0	HS - PL - 5181	18,0	10,0	0,4
	HS - PL - 5182	18,0	12,0	0,4
5,5	HS - PL - 5518	18,0	12,0	0,4
6,0	HS - PL - 6182	18,0	12,0	0,4
8,0	HS - PL - 8221	22,0	15,0	0,4
10,0	HS - PL - 1025	25,0	16,0	0,4

WSUWKI - SPRINGS DO KOŁKÓW

