

WSUWKI - SPRINGS

POD BLACHOWKRĘT



Materiał: stal sprężynowa

Powłoka: fosforatowana, ocynk biały

Materials: spring steel

Surface: phosphated, zinc plated

Ø	Grubość blachy Sheets Thickness P	Kod produktu Reference	Wymiary - Dimensions				
			A	B	C	E	Forma Form
3,6	0,6 - 1,0	HS - SU36 - 061	16,5	11,0	8,4	0,6	C
	1,6 - 2,0	HS - SU36 - 162	16,5	11,0	8,4	0,6	C
	0,8 - 1,5	HS - SU36 - 081	17,0	8,0	8,9	0,6	E
	1,2 - 1,6	HS - SU36 - 116	14,5	9,0	7,4	0,6	A
4,2	1,0 - 1,4	HS - SU42 - 114	16,0	11,0	8,4	0,6	C
	1,4 - 1,8	HS - SU42 - 118	16,0	11,0	8,4	0,6	C
	1,4 - 2,0	HS - SU42 - 142	19,0	12,0	8,4	0,7	C
4,8	0,9 - 1,1	HS - SU48 - 911	20,0	12,0	8,8	0,7	C
	1,0 - 2,0	HS - SU48 - 115	20,0	12,0	8,8	0,7	C
	1,2 - 1,6	HS - SU48 - 116	24,5	15,0	11,7	0,8	D
	0,7 - 1,2	HS - SU48 - 071	16,0	15,5	8,2	0,8	B

Ø	Grubość blachy Sheets Thickness P	Kod produktu Reference	Wymiary - Dimensions				
			A	B	C	E	Forma Form
5,5	1,4 - 2,2	HS SU55 - 142	25,0	15,5	14,5	0,8	A
6,3	1,4 - 2,2	HS SU63 - 122	25,0	15,5	14,5	0,8	E

