


DIN 985 - ISO 10511 - PN 82175

Norma

Nakrętka sześciokątna samozabezpieczająca z wkładką niemetalową



MATERIAŁY:

- Stal kl. 6, 8, 10,
- Stal nierdzewna A2, A4
- Mosiądz, Aluminium

POKRYCIA:

- O cynk galwaniczny
- O cynk płatkowy
- Inne na zapytanie

RODZAJE GWINTÓW:

- Metryczne
- Metryczne drobnozwojne

d	s	e	m	h
M 2,5	5,0	5,5	2,3	3,5
M 3	5,5	6,01	2,4	4,0
M 4	7,0	7,66	2,9	5,0
M 5	8,0	8,79	3,2	5,0
M 6	10,0	11,05	4,0	6,0
M 8	13,0	14,38	5,5	8,0
M 8 x 1	13,0	14,38	5,5	8,0
M 10	17,0	18,9	6,5	10,0
M 10 x 1	17,0	18,9	6,5	10,0
M 12	19,0	21,1	8,0	12,0
M 12 x 1,5	19,0	21,1	8,0	12,0
M 14	22,0	24,49	9,5	14,0
M 16	24,0	26,75	10,5	16,0
M 16 x 1,5	24,0	26,75	10,5	16,0
M 18	27,0	29,56	13,0	18,5
M 20	30,0	32,95	14,0	20,0
M 20 x 1,5	30,0	32,95	14,0	20,0
M 22	32,0	35,05	15,0	22,0
M 24	36,0	39,55	15,0	24,0
M 24 x 1,5	36,0	39,55	15,0	24,0
M 27	41,0	45,02	17,0	27,0
M 30	46,0	50,85	19,0	30,0
M 33	50	55,37	22	33
M 36	55	60,79	25	36
M 39	60	66,44	27	39
M 42	65	72,09	29	42
M 45	70	76,95	32	45
M 48	75	82,6	36	48

* Wymiary w tabeli to wymiary standardowe

** Inne na zapytanie