

HTS-Z/E A2

Stal nierdzewna » otwarte » kolnierz stożek » radełkowane

Stainless Steel » open end » countersunk head » knurled



Gwint Thread									kod		€ / 100szt.
M3	4,9	10,0	1,7-3,0	5,0	8,0	1,5			HTS-Z/E-3,0 M3 A2	250	14,5
		11,0	3,0-4,0						HTS-Z/E-4,0 M3 A2	250	15,2
M4	5,9	10,0	2,0-3,5	6,0	9,0	1,5			HTS-Z/E-3,5 M4 A2	250	15,2
		11,5	3,5-5,0						HTS-Z/E-5,0 M4 A2	250	16,4
M5	6,9	12,0	2,0-4,0	7,0	10,0	1,5			HTS-Z/E-4,0 M5 A2	250	17,9
		13,5	4,0-6,0						HTS-Z/E-6,0 M5 A2	250	18,6
M6	8,9	14,5	2,0-4,5	9,0	12,0	1,5			HTS-Z/E-4,5 M6 A2	250	22,1
		17,5	4,5-6,5						HTS-Z/E-6,5 M6 A2	250	24,5
M8	10,9	17,5	2,0-4,5	11,0	14,0	1,5			HTS-Z/E-4,5 M8 A2	250	29,2
		19,5	3,5-6,5		13,7				HTS-Z/E-6,5 M8 A2	250	31,2
M10	11,9	16,5	1,5-4,0	12,0	15,0	1,5			HTS-Z/E12-4,0 M10 A2	100	42,0
		18,5	3,0-6,0						HTS-Z/E12-6,0 M10 A2	100	44,6
M10	12,9	19,4	2,0-4,5	13,0	16,0	1,6			HTS-Z/E13-4,5 M10 A2	100	43,6
		23,4	3,5-6,5		15,7				HTS-Z/E13-6,5 M10 A2	100	47,2