










NITY STANDARDOWE – KOŁNIERZ PŁASKI

Aluminium / Aluminium - EN ISO 15981

STANDARD BLIND RIVETS – DOME HEAD

Aluminium / Aluminium – EN ISO 15981



								kod	
3,2 (+0,08/-0,10)	6,0	1,5-3,0	6,5 (+0/-0,7)	0,8 (+/-0,20)	3,1	670	535	AA030006	1000
	8,0	3,0-5,0						AA030008	1000
	10,0	5,0-7,0						AA030010	1000
	12,0	7,0-9,0						AA030012	1000
	14,0	9,0-11,0						AA030014	1000
	16,0	11,0-12,5						AA030016	1000
4,0 (+0,08/-0,15)	6,0	1,0-2,0	8,0 (+0/-1,0)	1,0 (+/-0,30)	4,1	1025	845	AA040006	1000
	8,0	2,0-4,0						AA040008	1000
	10,0	4,0-6,0						AA040010	1000
	12,0	6,0-8,0						AA040012	1000
	14,0	8,0-10,0						AA040014	500
	16,0	10,0-12,0						AA040016	500
	18,0	12,0-14,0						AA040018	500
	20,0	14,0-16,0						AA040020	500
4,8 (+0,08/-0,15)	8,0	2,0-3,5	9,5 (+0/-1,0)	1,1 (+/-0,30)	4,9	1425	1155	AA048008	500
	10,0	3,5-5,5						AA048010	500
	12,0	5,5-7,5						AA048012	500
	14,0	7,5-9,5						AA048014	500
	16,0	9,0-11,0						AA048016	500
	18,0	11,0-13,0						AA048018	500
	20,0	13,0-15,0						AA048020	500
	22,0	15,0-17,0						AA048022	500
	25,0	17,0-20,0						AA048025	500
	30,0	20,0-25,0						AA048030	250
	35,0	25,0-30,0						AA048035	250