










# NITY STANDARDOWE – KOŁNIERZ PŁASKI POWIĘKSZONY

Aluminium ( AlMg 3,5 ) / Stal ocynkowana - EN ISO 15977

## STANDARD BLIND RIVETS – LARGE HEAD

Aluminium ( AlMg 3,5 ) / Steel zinc plated – EN ISO 15977



								kod	
3,2 (+0,08/-0,10)	6,0	1,5-3,0	9,5 (+0/-0,5)	2,0	3,3	980	760	AS-LH9503206	500
	8,0	3,0-5,0						AS-LH9503208	500
	10,0	5,0-7,0						AS-LH9503210	500
	12,0	7,0-9,0						AS-LH9503212	500
	14,0	9,0-11,0						AS-LH9503214	500
4,0 (+0,08/-0,15)	6,0	1,0-2,0	12,0 (+0/-0,5)	2,5	4,1	1600	1200	AS-LH1204006	500
	8,0	2,0-4,0						AS-LH1204008	500
	10,0	4,0-6,0						AS-LH1204010	500
	12,0	6,0-8,0						AS-LH1204012	500
	14,0	8,0-10,0						AS-LH1204014	500
	16,0	10,0-12,0						AS-LH1204016	500
	18,0	12,0-14,0						AS-LH1204018	500
	20,0	14,0-15,5						AS-LH1204020	500
4,8 (+0,08/-0,15)	8,0	2,0-3,5	14,0 (+0/-0,5)	2,5	4,9	2230	1690	AS-LH1404808	500
	10,0	3,5-5,5						AS-LH1404810	500
	12,0	5,5-7,5						AS-LH1404812	250
	14,0	7,5-9,5						AS-LH1404814	250
	16,0	9,0-11,0						AS-LH1404816	250
	18,0	11,0-13,0						AS-LH1404818	250
	20,0	13,0-15,0						AS-LH1404820	250
	22,0	15,0-17,0						AS-LH1404822	250
	25,0	17,0-20,0						AS-LH1404825	250
	28,0	20,0-23,0						AS-LH1404828	250
	30,0	23,0-24,5						AS-LH1404830	250
	35,0	24,5-29,0						AS-LH1404835	250
	5,0 (+0,08/-0,15)	8,0						2,0-3,5	14,0 (+0/-0,5)
10,0		3,5-5,5	AS-LH1405010	250					
12,0		5,5-7,5	AS-LH1405012	250					
14,0		7,5-9,5	AS-LH1405014	250					
16,0		9,0-11,0	AS-LH1405016	250					
18,0		11,0-13,0	AS-LH1405018	250					
20,0		13,0-16,0	AS-LH1405020	250					
24,0		16,0-20,0	AS-LH1405024	250					
27,0		20,0-23,0	AS-LH1405027	250					
30,0		23,0-26,0	AS-LH1405030	250					










# NITY STANDARDOWE – KOŁNIERZ PŁASKI POWIĘKSZONY

Aluminium ( AlMg 3,5 ) / Stal ocynkowana - EN ISO 15977

## STANDARD BLIND RIVETS – LARGE HEAD

Aluminium ( AlMg 3,5 ) / Steel zinc plated – EN ISO 15977



								kod	
4,8 (+0,08/-0,15)	10,0	3,5-5,5	16,0 (+0/-0,5)	2,5	4,9	2230	1690	AS-LH1604810	250
	12,0	5,5-7,5						AS-LH1604812	250
	14,0	7,5-9,5						AS-LH1604814	250
	16,0	9,0-11,0						AS-LH1604816	250
	18,0	11,0-13,0						AS-LH1604818	250
	20,0	13,0-15,0						AS-LH1604820	250
	22,0	15,0-17,0						AS-LH1604822	250
	25,0	17,0-20,0						AS-LH1604825	250
	28,0	20,0-23,0						AS-LH1604828	250
	30,0	23,0-24,5						AS-LH1604830	250
35,0	24,5-29,0	AS-LH1604835	250						
5,0 (+0,08/-0,15)	10,0	3,5-6,0	16,0 (+0/-0,5)	2,5	5,1	2400	1600	AS-LH1605010	250
	12,0	6,0-8,0						AS-LH1605012	250
	14,0	8,0-10,0						AS-LH1605014	250
	16,0	10,0-12,0						AS-LH1605016	250
	18,0	12,0-14,0						AS-LH1605018	250
	20,0	14,0-17,0						AS-LH1605020	250
	24,0	17,0-20,0						AS-LH1605024	250
	27,0	20,0-23,0						AS-LH1605027	250
	30,0	23,0-26,0						AS-LH1605030	250