




HS88120

Podkładka sprężysta standardowa SCHNORR TYP S

MATERIAŁY:

- Stal
- Stal nierdzewna A2 1.4301

POWŁOKA:

- Bez pokrycia S
- O cynk mechaniczny ZM

Gwint	2	2.5	3	3.5	4	5	6
d1	2.2	2.7	3.2	3.7	4.3	5.3	6.4
d2	4	4.8	5.5	6	7	9	10
s	0.35	0.45	0.45	0.45	0.5	0.6	0.7
h	0.6	0.9	0.9	0.9	1	1.1	1.2
dla gwintu calowego	–	–	1/8"	–	5/32"	3/16"	–

Gwint	7	8	10	12	14	16	18
d1	7.4	8.4	10.5	13	15	17	19
d2	12	13	16	18	22	24	27
s	0.7	0.8	1	1.1	1.2	1.3	1.5
h	–	5/16"	3/8"	–	9/16"	5/8"	–
dla gwintu calowego							

Gwint	20	22	24	27	30	36
d1	21	23	25.6	28.6	31.6	38
d2	30	33	36	39	45	54
s	1.5	1.5	1.8	2	2	2.5
h	2.5	2.7	2.9	3.1	3.6	4.2
dla gwintu calowego	–	7/8"	–	–	1 1/8"	1 3/8"