


Nakrętka wywijana ARB



- Nakrętka wywijana ARB

MATERIAŁY:

- Stal

POWŁOKA:

- O cynk biały ZI

Wymiary

Rozmiar gwintu (calowy)	Rozmiar gwintu (metryczny)	Średnica kołnierza (A) [mm]	Średnica nakrętki (B) [mm]	Wysokość nakrętki (C) [mm]	Wysokość gwintu (D) [mm]	Otwór montażowy [mm]
4	M2.5 / M3	5.8	7.9	3.2	3.3	5.90
6	M3.5 / M4	6.9	9.5	3.9	3.8	6.95
8	M4	6.9	9.5	3.9	3.8	6.95
10	M5	8.3	11.1	4.6	4.4	8.35
1/4	M6	9.5	12.7	5.7	5.9	9.65
5/16	M8	13.0	15.9	6.5	6.4	13.10
3/8-7/16	M10	15.4	19.1	7.9	7.6	15.50
1/2	M12	19.4	25.4	10.2	10.4	19.50

Kod kołnierza	001	003	004	006	008	010	012	013	014
Grubość blachy [mm]	0.5 – 0.6	0.7 – 0.8	0.9 – 1.0	1.1 – 1.3	1.4 – 1.6	1.7 – 1.9	2.0 – 2.2	2.3 – 2.5	2.6 – 2.8
Kod kołnierza	016	017	018	019	020	022	023	024	026
Grubość blachy [mm]	2.9 – 3.1	10swg	3.2 – 3.4	3.5 – 3.7	3.8 – 4.0	4.1 – 4.3	4.4 – 4.6	4.7 – 4.9	5.0 – 6.0

Sposób zamówienia

ARB	
Nazwa produktu	ARB-M4-008-S-Z
Gwint	ARB-M4-008-S-Z
Kod kołnierza	ARB-M4-008-S-Z
Materiał	ARB-M4-008-S-Z
Powłoka	ARB-M4-008-S-Z